

LIGHTING STAND

483T 3 SCT Wind-Up Stand w/Auto Self-Locking device

L 181cm
71.3"

H 380cm
149.7"

W 22.4kg
49.4lbs

max 128cm
50.4"

max 30kg
66.1lbs

max KC-100



3 sections.

Dia.: 55mm, 45mm, 38mm

Leg dia.: 30mm

Chrome plated steel stand
w/geared column.

2 risers extend simultaneously at one
elevation of 4.4cm per handle turn.

Safety cable ensures simultaneous
retrieval of all sections.

With 1 leveling leg

Auto Self-Locking device
stop unexpected drop-off,
and make operation safer.
(PAT.ZL2006201577133.0)



Lock position

The safety pin will auto
insert to the holey tube
when wind-up.



Unlock position

The inside spring will bring
the safety pin back.



483-BP Base Plate
Set for three available with
481,482, 483T, 470 stands



Features of Wind-up stand :

The stand top mounted by a steel bolt
through the top tube that offers most
sturdy and solid assembly.



The tension of break shoe can be
adjusted with Allen wrench.



To prevent the tube falling off rapidly,
the wind-up handle should be inserted
in between center pole and legs.



Leveling legs should be set into
horizontal at leaning location.



Velcro is supplied to fasten the legs
for better storage and transportation.



Top section tube can be adjusted by
stepping on foot step.



Casters are optional for easily moving
the stand. The stand foot is rugged
zinc-casting. Dia.: 100mm with brake
and M10 attachment. A set is for three
(KC-100).



OPTIONAL ACCESSORY
KS-056 LATERN BAR
6 x lantern T Bar
1420mm long with
Dia. 28mm stud