

MSR Gold™ FastFit

MSR Gold™ 1200 FastFit 1CT

Product data

• General Characteristics

System Description FastFit

Cap-Base PGJX50

Cap-Base Information PGJX50

Execution -

Operating Position any

Main Application Entertainment

Life to 50% failures

EM

750 hr

• Light Technical Characteristics

Color Code -

Color Rendering

Index

80 Ra8

Color Temperature 6000 K

Color Temperature

Technical

6000 K

Chromaticity Coordinate

X

318 -

Chromaticity Coordinate

Y

327 -

Luminous Flux Lamp

EM

79500 (min), 95000 (nom) Lm

Luminous Efficacy

Lamp EM

80 Lm/W

• Electrical Characteristics

Lamp Wattage 1200 W

Lamp Wattage Technical

1200 W

Lamp Current 15 A

Ignition Supply

Voltage

198 (min) V

Dimmable Yes

• Luminaire Design Requirements

Pinch Temperature 500 (max) C

Bulb Temperature 950 (max) C

• Product Dimensions

Overall Length C 128 (max) mm

Diameter D 26.1 (max) mm

Width F 41 mm

Light Center Length

L

64 (min), 65 (nom), 66 (max) mm

Arc Length O 5.5 mm

• Product Data

Order code 928175005114

Full product code 928175005114

Full product name MSR Gold™ 1200 FastFit 1CT

Order product name MSR Gold 1200 FastFit 1CT/8

Pieces per pack 1

Packing configuration 8

Packs per outerbox 8

Bar code on pack -

EAN1

8727900908565

Bar code on

outerbox - EAN3

8727900908572

Logistic code(s) -

12NC

928175005114

Net weight per piece 0.147 kg