

# MSR Gold™ SA Double Ended

MSR Gold™ 1200 SA/DE 1CT

## Product data

### • General Characteristics

System Description SA/DE  
Cap-Base SFC10-4  
Cap-Base Information SFC10-4  
Execution -  
Operating Position any  
Main Application Entertainment  
Life to 50% failures  
EM  
750 hr

### • Light Technical Characteristics

Color Code -  
Color Rendering  
Index  
85 Ra8  
Color Temperature 6000 K  
Color Temperature  
Technical  
6000 K  
Chromaticity Coordinate  
X  
326 -  
Chromaticity Coordinate  
Y  
332 -  
Luminous Flux Lamp  
EM  
98000 (min), 106000 (nom) Lm  
Luminous Efficacy  
Lamp EM  
91 Lm/W

### • Electrical Characteristics

Lamp Wattage 1200 W  
Lamp Wattage Technical  
1200 W  
Lamp Current 13.6 A  
Ignition Supply  
Voltage  
198 (min) V  
Dimmable No

### • Luminaire Design Requirements

### • Product Dimensions

Base Face to Base  
Face A  
114.4 (min), 114.8 (nom), 115.2 (max)  
mm  
Overall Length C 136 (max) mm  
Diameter D 22 (max) mm  
Arc Length O 7.0 mm

### • Product Data

Order code 928099605114  
Full product code 928099605114  
Full product name MSR Gold™ 1200 SA/DE 1CT  
Order product name MSR Gold 1200 SA/DE 1CT/16  
Pieces per pack 1  
Packing configuration 16  
Packs per outerbox 16  
Bar code on pack -  
EAN1  
8727900904970  
Bar code on  
outerbox - EAN3  
8727900904987  
Logistic code(s) -  
12NC  
928099605114  
Net weight per piece 0.034 kg